

PRT® (ES)

Environmentally Sealed PRT Heat Shrink Wrap



Environmentally Sealed

Prevent water from penetrating your wire or cable repair.

PRT® (ES) combines the proven characteristics of a wrap-around, heat-shrinkable tubing with the added benefits of using Z-Block® hot-melt adhesive. PRT® (ES) is designed to provide water blocking and creates an environmentally sealed repair patch for wires and cables.



Environmentally sealed using Z-Block® hot-melt adhesive. PRT® (ES) is available with either Z-Block® (100) or Z-Block® (135). See "Z-Block®" on Page c16



Water Blocking

PRT® (ES-100) hot-melt starts melting at 212°F
PRT® (ES-135) hot-melt starts melting at 275°F



REQUEST A QUOTE
ONLINE OR OVER
THE PHONE

Specifications

Durability	★ ★★ ★★★ Good Better Best	Elongation	200% (after shrink)
Material Type	Cross-linked polyolefin	Fluid Resistance	Excellent
Operational Temp	-67° to 212 / 275°F -55° to 100 / 135°C	Dielectric Strength	500v/mil (after shrink)
RoHS	Yes	Tensile Strength	1500 psi. (after shrink)
Material Thickness	0.035" - 0.055"	Mil-Spec	SAE-AMS- DTL-23053/5
Shelf Life	24 months	Fungicide	No growth
Flame Retardant	UL224, VW-1, self-extinguishing		

ZT
zippertubing

www.zippertubing.com

855.289.1874