

# Z-Wrap®

Lightweight Wrap-Around Jacket System

## Toolless Installation

This closure allows installation without the need for secondary tooling on assemblies that do not require re-entry and where a "pull-through" jacket is undesirable.

**Z-Wrap®** is an economical, lightweight, wrap-around jacket system for round, flat, or rectangular cables that uses Zippertubing's type PVL-10, RPU-17, or DVH-20 materials and a pressure-sensitive adhesive closure. A strip of high-strength, specially formulated acrylic adhesive is bonded to one edge to provide a secure and flexible closure. The thin and highly flexible adhesive closure allows for extremely tight cable bends. Z-Wrap® is ideal for discrete wires, wire harnesses, hoses, and other applications where flexibility, strength, and abrasion protection are needed.













The thin and highly flexible adhesive closure allows for extremely tight cable bends



REQUEST A QUOTE  
ONLINE OR OVER  
THE PHONE

## Available Jackets

	PVL-10	DVH-20	RPU-17
 <b>Durability</b>	★ Good	★★★ Best	★★★ Best
 <b>Material Type</b>	PVC-coated polyester	PVC-coated polyester	Reinforced polyurethane (Non-PVC)
 <b>Operational Temp</b>	-40° to 180°F -40° to 82°C	-22° to 185°F -30° to 85°C	-40° to 160°F -40° to 71°C
 <b>RoHS</b>	Yes	Yes	Yes
 <b>Material Thickness</b>	0.010"	0.020"	0.017"
 <b>Color Options</b>			
 <b>Flame Retardant</b>	FED-STD-191 Method 5903	Fed-Std-191A Method 5903 - 2 sec max	NFPA-701 (2 sec) & FAR- 25.853a 12 sec vertical

**ZT**  
zippertubing



zippertubing.com



855.289.1874