

# Zip-Wrap®

Lightweight, Abrasion-Resistant Zippered Sleeve

## Versatile Jacketing

This product is well suited for any round, flat, or rectangular cable bundling application. You now have the ability to quickly wrap, zip, and enjoy.

**Zip-Wrap®** (PVL) is a lightweight, abrasion-resistant, zipper sleeve comprised of flame-retardant polyester fabric that is coated with polyvinyl chloride (PVC) on both sides.

Zip-Wrap® utilizes a molded nylon tooth plastic zipper, PVL-10-coated fabric jacket material and is sewn together using nylon thread. The zipper closure allows for a seamless installation without the need for tooling on assemblies that require re-entry after installation.

Thermal Option See "Zip-Wrap® (ALP-500)" on Page c35
















**Many Options Available**

Resistant to acids, salts, bases, alcohols, and mild solvents. Great for both indoor and outdoor applications



REQUEST A QUOTE  
ONLINE OR OVER  
THE PHONE

## Specifications

 <b>Durability</b>	★   ★★   ★★★ Good   Better   Best	 <b>Fluid Resistance</b>	Hydro resist - 150 psi.
 <b>Material Type</b>	PVC-coated polyester	 <b>Flame Retardant</b>	FED-STD-191 method 5903
 <b>Operational Temp</b>	-40° to 180°F -40° to 82°C	 <b>Mil-Spec</b>	MIL-C-43006G, type II, class 1
 <b>RoHS</b>	Yes	 <b>Flexibility</b>	Excellent
 <b>Material Thickness</b>	0.010"	 <b>Jacket Color Options</b>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
 <b>Shelf Life</b>	36 months	 <b>Closure Type</b>	Nylon zipper <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
 <b>Tensile Strength</b>	120 lbs (warp) 100 lbs (fill)		

**ZT**  
zippertubing

 [zippertubing.com](http://zippertubing.com)

 855.289.1874